

GT06 GPS vehicle Tracker



GT06

G_{T06}: Features & Technical Details

Features:

- GSM 850/900/1800/1900 Quad band
- Compact & waterproof design
- Wide for voltage input range:9-36vDC
- GPS continuous positioning, GPRS timing interval
- Check location via SMS
- Built-in vibration sensor, theft proof
- ACC ignition detection
- Tele-cut off (petrol/ electricity) function
- SOS alarm and burglar alarm
- Voice monitor function
- Alarm when the power supply is disconnected intentionally (with backup battery)
- Internal GSM & GPS Antenna
- Compatible with external connection through serial port

Technical Details:

Items	Specification
Charging Voltage	DC 5v – 36vdc
Internal Battery	Rechargeable and removable battery
Dimension	98 mm × 52 mm × 15 mm
Weight	80g (with battery)
Operating temperature	-25° to 70° C
Humidity	5% to 95% Non-condensing
GSM module	Quad Band GSM 850/900/1800/1900Mhz
GPS Chipset	Latest GPS SIRF-Star III chipset
GPS Sensitivity	-159Db
Memory	1 MB
Channels	20 channel all-in-view tracking
Position Accuracy	+/- 5 meters, 2D RMS
Velocity Accuracy	0.1 m/s
Hot start	<2 sec.
Warm start	<15 sec
Cold start	<38 sec
LED	3 LEDs to show power, GPS, GSM and other status.
Casing/Sealing	Waterproof

Design and specifications subject to change without notice.

GTI Infotel

150 Pocket 1, Jasola, New Delhi 110025

info@gtiinfotel.com

<http://www.gtiinfotel.com>

Mobile: +91-9911004651

Works: 0120-427-3656; HQ: 011-2994-3338



GTI Infotel

An ISO 9000:2008 Company